

LUBRANOL SN

880/16/10/08/B1

COMMERCIAL FORM Yellow limpid liquid.

APPLICATIONS Synthetic (soap free) lubricant with sanitising action for use on chain conveyor systems suitable for automatic jetting.

COMPOSITION Product based on cationic and non ionic surfactants.

PROPERTIES LUBRANOL SN is a highly efficient lubricant suitable at recommended concentration for all conveyors even at speeds in excess of 40,000 units/hour.
LUBRANOL SN has a very powerful detergent action, quickly removing all deposits and a sanitising power.

This product can be applied in the food industry (brewery, soft drink, etc.) and meets all national and European related legislations currently in force.

USE CONCENTRATION 0.1 - 0.25 % v/v depending on the installation.
The pH of the working solution should preferably be situated between 7 and 9.

IMPORTANT REMARK Prior to carry out a practical trial :

If the old lubricant was a soap, it is very important to clean the pipe lines and jets thoroughly to remove all traces of the old lubricant prior to use LUBRANOL SN.

CONCENTRATION ANALYSIS Titration method by means of test kit.

For more details on the method and test kit, please contact your Sopura technical responsible in charge for your region.

Specific gravity : 0.995 +/- 0.015

PACKAGING Jerrycan - drum - IBC on request.

STORAGE Protect from freezing (crystallisation point : ca 0°C).

LUBRANOL SN

880/16/10/08/B2

FIRST AID re : material safety data sheet.

SAFETY PRECAUTIONS re : material safety data sheet.

TRANSPORT ADR-RID :
IMO : re : material safety data sheet.